

READ INFORMATION COMPLETELY PRIOR TO USE

► See Updated Care & Use Instructions and Translations @ WWW.SIDESHIELD.COM

NOTICE: This SideWear® shield provides LIMITED eye protection. It has been tested by an independent testing laboratory and certified compliant to the high velocity impact requirements of ANSI Z87.1-2010 however it will not protect against all possible eye hazards. This test procedure does not suggest that this product is indestructible, unbreakable or impenetrable.

CAUTION: NEVER use this product to protect against severe hazards such as but not limited to explosives, fragmenting grinding wheels or abrasive discs, molten metal, lasers, welding, brazing, torch cutting, nail guns, sports activities, simulated war or paintball games or similar activities. Use additional appropriate protective equipment such as face shields. Dress eyewear is not compliant to ANSI Z87.1 and even when equipped with SOS compliant SideWear® components, this combination shall not be worn in an industrial work environment. Environmental and/or Atmospheric conditions can cause fogging of lenses and may impact Expected performance. Frequent cleaning may be required. If at any time vision is or may be impaired the user should take immediate precautions for personal safety then notify appropriate Supervisor and Safety Professional for assistance.

WARNING: MAINTENANCE & CARE is important to a continuing level of protection. Contact with certain chemicals, including those in some sunscreens, bug repellents and lens cleaners may cause a substantial reduction in impact resistance. To clean, wash in a mild soap solution and rinse in clean water. Do not exceed Min/Max range of sideshield selection guideline (see pg 1). INSPECT product (lens & mounting band) prior to each use for pits, scratches, cracks, crazing or discoloration and replace when any of these conditions exist. Scratched and dirty devices reduce vision, increase glare and may contribute to accidents or premature failure.

WARRANTY: SOS warrants to purchaser of its SideWear® that these products are free of defects in material and workmanship for a period of one year from date of purchase. If the product is found defective in materials or workmanship and returned to SOS within the warranty period, it will be replaced. Replacement constitutes the sole remedy for breach of this warranty. Unless prohibited by applicable law, Safety Optical Service Disclaims all other expressed or implied warranties and shall not have any other obligation or liability. This warranty does not apply to defects or damage from misuse, alteration, use of unapproved cleaning agents, improper fit on glasses with which the product is used or use unintended by SOS. In particular, this warranty does not apply to, and SOS is not responsible for, any defect, damages or loss suffered or incurred where our universal SideWear® is attached to frames which have not been tested to the applicable paragraphs of ANSI Z87.1-2010.

SOS SideWear® Shields comply with OSHA 29CFR1910 / Conformity to ANSI Z87.1-2010 has been assessed per ANSI/ISEA 125-2014 level 1 by INDEPENDENT TESTING LABORATORY and found COMPLIANT.

Distribute one with each set of Sideshields.

IMPORTANT INFORMATION

- Proper Selection
- Simple Adjustment
- Mounting Instructions
- Required Maintenance



WHICH SIDEWEAR™ IS RIGHT FOR YOU?



Best Fit for:

- Small Frames
- Medium Frames
- Large Frames

The following measurements are given as selection guidelines:
1.182" to 1.70" (30mm to 43mm)



Best Fit for:

- Small Frames
- Medium Frames
- Large Frames

The following measurements are given as selection guidelines:
1.25" to 2.125" (32mm to 54mm)

Care & Use Instructions

Universal SideWear™ ANSI Z87.1-2010 Compliant

Call or E-mail for the location of your nearest distributor:

WWW.SIDESHIELD.COM
TOLL FREE: 866-919-2020

Patent No. 5,748,276, 6,393,609 B1 and others

1 ADJUSTMENT IS SIMPLE



Larger Frames:
Open Sideshield until slightly smaller than frame size and install.



Average Frames:
Ensure Sideshield is slightly smaller than frame size and install.




Smaller Frames:
Close Sideshield until slightly smaller than frame size and install.

After selecting Sideshield, some minor adjustment may be necessary to obtain proper fit.

Our exclusive patented Living Hinge™, permits adjustments to larger, average and smaller frames.

Refer to selection guidelines on pg.1 for min/max adjustment of side shields for small, medium and large safety frames.

2 MOUNTING IS EASY



1 • Insert LEFT temple **through large loop** of black mounting band on the inside of the LEFT sideshield (Fig. 1)

2 • Hold frame and sideshield firmly while **stretching the band** outward and back to fit into the retaining grooves and over the rear tab. (Fig. 2)

3 • Inspect the sideshield alignment to be certain the frame is centered **between the top and bottom ribs**. Then, repeat these steps for the right side.

4 • The sideshields are now affixed to the frame front and temples will fold without the sideshields moving.